

FEATURES & OVERVIEW

The IQ Siren is a wireless Z-Wave device that allows you to have additional sirens placed throughout the home.

It plugs into any standard outlet, acts as a repeater in the Z-Wave network, has a rechargeable back up battery and three LED lights that strobe when the siren is triggered.

Mounting Locations:

- Kitchen
- Living Room
- Basement
- Bedrooms
- Garage

Pair up to 3 IQ Sirens with the IQ Panel.

SPECIFICATIONS

Built-in Lithium Battery: 430 mAh

Alarm Power: 1.7W

Max Standby Power: 0.7W

Max Volume: 105dB

Operating Temperature: 0°C to 40°C

Operating Distance: Up to 550 feet outdoors

Frequency Type : Z-Wave Plus



STEP 1
DETERMINE
INSTALLATION
LOCATION



Plug in the IQ Siren
at desired location

STEP 2
PREPARE THE IQ PANEL TO
ENROLL THE IQ SIREN



Place your panel in
"autolearn" mode



STEP 3
PAIRING WITH
THE IQ PANEL



Press the button on
the bottom of the IQ
Siren once to enroll
with the IQ Panel.
(LED will flash)



Customize name



Complete pairing process
by touching **Add**



Test device to ensure
proper function

Document#: IQSIREN-QG-03-17
Revision#: 03/27/17
Issue Date: MAR 2017
Golsys Product #: QZ2300-840

Golsys Inc. proprietary.
Reproduction without permission is not permitted.
FCC ID: XBAZW080

GOT QUESTIONS?
CONTACT TECH SUPPORT
TechSupport@Golsys.com

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Cet appareil est conforme avec Industrie Canada exempts de licence standard RSS (s). Son fonctionnement est soumis aux deux conditions suivantes: (1) cet appareil ne doit pas provoquer d'interférences et (2) cet appareil doit accepter toute interférence, y compris celles pouvant causer un mauvais fonctionnement de l'appareil.